






Product data sheet

August 16th, 2023

Product			
Trade name:		Description:	
Maxx 130		<ul style="list-style-type: none"> • Permanent marker with bullet tip • line width 1 - 3 mm. • For writing on cardboard, paper, plastic, glass, metal, wood and almost all other materials • quick-drying, water-proof and light resistant • cap-off ink, does not dry out if the cap is removed for 2-3 days • low-odour, free of toluene and xylene • practical clip cap • can be refilled using Maxx 640 refill station • *Pen body consists of 95% recycled plastics, internal ink reservoir of 75% recycled fibres. <p>The recycled plastic is tested for harmful substances, according to the toy standard EN 71-3 and verifiably consists of 100% recyclate. The recyclate content is confirmed by the independent certifier DIN CERTCO (register no. 8Y0003), according to the test regulations of DIN EN ISO 14021 and DIN EN 15343.</p> 	
Line width:	1 – 3 mm		
Article No.	Writing colour		Internal No.
113001	black		466591
113002	red		466592
113003	blue		466593
113004	green		466594
113005	yellow		466595
113006	orange		466596
113007	brown		466597
113008	violet	466598	
			
Recycled plastic Barrel	Internal material number 458479		



Components	
Used material:	Ink:
Recycled plastic material: Polypropylene (PP) Polyester (PET, 75% recycled fibres) Acrylic	Filling per pen: 3.35 g
	Alcohol-based ink. Includes solvents, colorants and additives.

Indication for security and environment

Barrel:

Hazardous ingredients

None according to EU directives

Ink:

The information in this section is based on the safety data sheet according to Regulation (EC) No. 1907/2006 (REACH). All stated contents are provided in percentage by weight.

Writing colour black

Hazardous ingredients

1-Methoxypropan-2-ol CAS 107-98-2
25-<50%

Propan-1-ol CAS 71-23-8
25-<50 %

Classification of the mixture:



GHS02 Flame
Flam. Liq. 3/H226
H226 Flammable liquid and vapour.



GHS05 Caustic
Eye Dam. 1//H318
H318 Causes serious eye damage.



GHS07
STOT SE 3/H336
H336 May cause drowsiness or dizziness.

Writing colour red

Hazardous ingredients

1-Methoxypropan-2-ol CAS 107-98-2
50-<75%

Propan-1-ol CAS 71-23-8
25-< 50 %

C. I. Solvent Yellow 82 CAS 85029-58-9
3-<5%

C. I. Solvent Red 49 CAS 509-34-2
1-<3%





Classification of the mixture:












GHS02 Flame
Flam. Liq. 3/H226
H226 Flammable liquid and vapour.



GHS05 Caustic
Eye Dam. 1/H318
H318 Causes serious eye damage.

	<div style="display: flex; align-items: flex-start;"> <div style="margin-right: 10px;">  </div> <div> <p>GHS07 Skin Sens. 1/H317 H317 May cause an allergic skin reaction. STOT SE 3/H336 H336 May cause drowsiness or dizziness</p> <p>Aquatic Chronic 3/H412 H 412 Harmful to aquatic life with long lasting effects.</p> <p><u>Writing colour blue</u></p> <p>Hazardous ingredients</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 70%;">1-Methoxypropan-2-ol 50—<75%</td> <td style="width: 30%; text-align: right;">CAS 107-98-2</td> </tr> <tr> <td>Propan-1-ol 25—< 50%</td> <td style="text-align: right;">CAS 71-23-8</td> </tr> <tr> <td>Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. 3—<5%</td> <td style="text-align: right;">CAS 85536-14-7</td> </tr> <tr> <td>C.I. Solvent Blue 51 1-<3%</td> <td style="text-align: right;">CAS 68411-04-1</td> </tr> <tr> <td>C. I. Solvent Violet 8 1-<3%</td> <td style="text-align: right;">CAS 561-41-1</td> </tr> </table> <p>Classification of the mixture:</p> <div style="display: flex; align-items: flex-start; margin-bottom: 10px;"> <div style="margin-right: 10px;">  </div> <div> <p>GHS02 Flame Flam. Liq. 3/H226 H226 Flammable liquid and vapour.</p> </div> </div> <div style="display: flex; align-items: flex-start; margin-bottom: 10px;"> <div style="margin-right: 10px;">  </div> <div> <p>GHS05 Caustic Eye Dam. 1/H318 H318 Causes serious eye damage.</p> </div> </div> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 10px;">  </div> <div> <p>GHS07 Skin Irrit. 2/H315 H315 Causes skin irritation. STOT SE 3/H336 H336 May cause drowsiness or dizziness.</p> </div> </div> <p><u>Writing colour green</u></p> <p>Hazardous ingredients</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 70%;">1-Methoxypropan-2-ol 50-<75%</td> <td style="width: 30%; text-align: right;">CAS 107-98-2</td> </tr> <tr> <td>Propan-1-ol 25—<50%</td> <td style="text-align: right;">CAS 71-23-8</td> </tr> <tr> <td>C.I. Solvent Blue 38 5-<10%</td> <td style="text-align: right;">CAS 1328-51-4</td> </tr> <tr> <td>C. I. Basic Yellow 37 1-<3%</td> <td style="text-align: right;">CAS 6358-36-7</td> </tr> <tr> <td>C. I. Basic Blue 7 0,1-<1%</td> <td style="text-align: right;">CAS 2390-60-5</td> </tr> </table> <p>Classification of the mixture:</p> </div> </div>	1-Methoxypropan-2-ol 50—<75%	CAS 107-98-2	Propan-1-ol 25—< 50%	CAS 71-23-8	Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. 3—<5%	CAS 85536-14-7	C.I. Solvent Blue 51 1-<3%	CAS 68411-04-1	C. I. Solvent Violet 8 1-<3%	CAS 561-41-1	1-Methoxypropan-2-ol 50-<75%	CAS 107-98-2	Propan-1-ol 25—<50%	CAS 71-23-8	C.I. Solvent Blue 38 5-<10%	CAS 1328-51-4	C. I. Basic Yellow 37 1-<3%	CAS 6358-36-7	C. I. Basic Blue 7 0,1-<1%	CAS 2390-60-5
1-Methoxypropan-2-ol 50—<75%	CAS 107-98-2																				
Propan-1-ol 25—< 50%	CAS 71-23-8																				
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. 3—<5%	CAS 85536-14-7																				
C.I. Solvent Blue 51 1-<3%	CAS 68411-04-1																				
C. I. Solvent Violet 8 1-<3%	CAS 561-41-1																				
1-Methoxypropan-2-ol 50-<75%	CAS 107-98-2																				
Propan-1-ol 25—<50%	CAS 71-23-8																				
C.I. Solvent Blue 38 5-<10%	CAS 1328-51-4																				
C. I. Basic Yellow 37 1-<3%	CAS 6358-36-7																				
C. I. Basic Blue 7 0,1-<1%	CAS 2390-60-5																				

	<p>  GHS02 Flame Flam. Liq. 3/H226 H226 Flammable liquid and vapour. </p> <p>  GHS05 Caustic Eye Dam. 17H318 H318 Causes serious eye damage. </p> <p>  GHS07 STOT SE 3/H336 H336 May cause drowsiness or dizziness. </p> <p> Aquatic Chronic 3/H412 H 412 Harmful to aquatic life with long lasting effects. </p> <p><u>Writing colour yellow</u></p> <p>Hazardous ingredients</p> <table data-bbox="813 840 1436 1120"> <tbody> <tr> <td>Ethanol 25 – 50 %</td> <td>CAS 64-17-5</td> </tr> <tr> <td>1-Methoxypropan-2-ol 25 – 50 %</td> <td>CAS 107-98-2</td> </tr> <tr> <td>Basic Yellow 37 ≤ 2.5 %</td> <td>CAS 6358-36-7</td> </tr> <tr> <td>C. I. Solvent Yellow 82 ≤ 1.0 %</td> <td>CAS 85029-58-9</td> </tr> </tbody> </table> <p>Classification of the mixture:</p> <p>  GHS02 Flame Flam. Liq. 2/H225 H225 Highly flammable liquid and vapour. </p> <p>  GHS07 Eye Irrit. 2/H319 H319 Causes serious eye irritation. STOT SE 3/H336 H336 May cause drowsiness or dizziness. </p> <p><u>Writing colour orange, brown</u></p> <p>Hazardous ingredients</p> <table data-bbox="813 1556 1404 1691"> <tbody> <tr> <td>1-Methoxypropan-2-ol < 65 %</td> <td>CAS 107-98-2</td> </tr> <tr> <td>Propan-2-ol < 20 %</td> <td>CAS 67-63-0</td> </tr> </tbody> </table> <p>Classification of the mixture:</p> <p>  GHS02 Flame Flam. Liq. 2/H225 H225 Highly flammable liquid and vapour. </p> <p>  GHS07 Eye Irrit. 2/H319 H319 Causes serious eye irritation. STOT SE 3/H336 H336 May cause drowsiness or dizziness. </p>	Ethanol 25 – 50 %	CAS 64-17-5	1-Methoxypropan-2-ol 25 – 50 %	CAS 107-98-2	Basic Yellow 37 ≤ 2.5 %	CAS 6358-36-7	C. I. Solvent Yellow 82 ≤ 1.0 %	CAS 85029-58-9	1-Methoxypropan-2-ol < 65 %	CAS 107-98-2	Propan-2-ol < 20 %	CAS 67-63-0
Ethanol 25 – 50 %	CAS 64-17-5												
1-Methoxypropan-2-ol 25 – 50 %	CAS 107-98-2												
Basic Yellow 37 ≤ 2.5 %	CAS 6358-36-7												
C. I. Solvent Yellow 82 ≤ 1.0 %	CAS 85029-58-9												
1-Methoxypropan-2-ol < 65 %	CAS 107-98-2												
Propan-2-ol < 20 %	CAS 67-63-0												

	<p>Writing colour violet</p> <p>Hazardous ingredients</p> <p>1-Methoxypropan-2-ol < 70 % CAS 107-98-2</p> <p>Propan-2-ol < 20 % CAS 67-63-0</p> <p>Solvent Red 218 < 5 % CAS 73049-38-4</p> <p>Classification of the mixture:</p> <p> GHS02 Flame Flam. Liq. 2/H225 H225 Highly flammable liquid and vapour.</p> <p> GHS07 Eye Irrit. 2/H319 H319 Causes serious eye irritation.</p> <p>STOT SE 3/H336 H336 May cause drowsiness or dizziness.</p>
<p>Flashpoint: none</p>	<p>Flashpoint: Writing colour black, red, blue, green: 23 °C Writing colour yellow: 13 °C Writing colour orange, brown, violet: 12 °C</p>
<p>Solubility in water: insoluble</p>	<p>Solubility in water: miscible</p> <p>Contact with skin: Wash with water and soap, do not use solvents.</p>
<p>Extinguishing media:</p> <ul style="list-style-type: none"> • Water spray • CO₂ • Dry-chemical fire extinguisher • Foam 	<p>After swallowing: Rinse mouth with water. In case of persistent symptoms consult doctor.</p> <p>After eye contact: Remove contact lenses. Rinse opened eye for several minutes under running water. Then consult a doctor.</p> <p>Odour: Alcoholic / ethereal odour. No dangerous concentration of alcoholic vapour during application.</p>
<p>Disposal: Environmentally friendly. No contamination of air or ground water in combusting plant. Empty refills can be disposed off with daily garbage considering local regulations.</p>	<p>Disposal: <u>Europe</u> According to local regulation, ex. to dispose of as colours. European waste catalogue "Code 080111".</p>

The information in this product data sheet refers to commercial quantities of finished products. It may not be always applicable for materials and preparations used for industrial processing.

The above mentioned data are based on our today's knowledge. They don't guarantee characteristics. Users of our products have to consider present laws and regulations in own responsibility. This product data sheet is not subject to an updating service.

Schneider has been certified as the first company of the writing instruments industry since 1998 after the world's most stringent environmental management system EMAS.